# SCREAMIN' PEARLS<sub>tm</sub>

### **Description**

Screamin' Pearls<sub>tm</sub> are based on the latest in pearlescent technology, Xyrellic pearls, that produces brilliant sparkle and provides clean side tones to maximize chromaticity of your base color. Screamin' Pearls<sub>tm</sub> have been treated with compounds to reduce dusting, make it easy to incorporate into solvent or waterborne paint, and provide a durable long lasting finish. Screamin' Pearls<sub>tm</sub> are a great choice for any kustom or hobby project!





# **Components**

SP-01	Screamin' Crystal White	SP-06	Screamin' Crystal Trans Red
SP-02	Screamin' Crystal Green	SP-07	Screamin' Crystal Deep Red
SP-03	Screamin' Crystal Blue	SP-08	Screamin' Crystal Purple
SP-04	Screamin' Crystal Yellow	SP-09	Screamin Turquoise
SP-05	Screamin' Crystal Copper		



# Mixing with Inter-Coat Clear

Mix 1-2 Table Spoons of Screamin' Pearl<sub>tm</sub> per unreduced quart of IC-101 Pearl, Flake, and Powder Binder. Mix well then reduce 2:1 with UreKem UR Series Reducer. Mix well to disperse pearl and strain with a medium paint filter before using.



#### Mixing with 2K Clearcoat

Screamin' Pearl<sub>tm</sub> may also be mixed with 2K polyurethane clearcoat for applications. Begin by activating and reducing your clearcoat per manufacturer's recommendations then add 1-2 table spoons of Screamin Pearl<sub>tm</sub> per spray able quart of clear. Most people find it helpful to add a small excess of reducer to help the pearls orient for best brilliance.

Each Screamin' Pearl bottle contains approximately 4 table spoons or 25 grams of material which is enough to paint the average sized vehicle when mixed for spray. Mix well to disperse pearl and strain with a fine paint filter before using.



# **Application**

In general you should apply 1-2 coats of clear mixed with your pearl with 50-75% overlap to ensure good pearlescent orientation. Allow adequate flash time between coats. May be used with conventional spray guns or large tipped airbrush. For best results do not apply "dry" or fog pearl onto substrate. Spray medium wet for best orientation of the pearl.

Read MSDS of all components before using. Use proper personal protective equipment at all times. For use by professionally trained painters. **KEEP OUT OF REACH OF CHILDREN.** Bayou Innovations, LLC warrants that its products are free from defects at time of shipping. All other warranties and guaranties of any kind whether expressed or implied are disclaimed.