

Material Safety Data Sheet (MSDS)

Section 1: Identification

Manufacturer: Bayou Innovations, LLC (Owner: UreKem Brand)
Address: 7350 Bayou La Croix Rd
Bay St Louis, Ms 39520

Products:
Prepared By: Regulatory Compliance Manager
24 hour 7 Day Emergency Response: Call ChemTel at 1-800-255-3924 (contract# MIS0007444)
D.O.T. Shipping Name: Paint, Flammable Liquids, UN 1263



Section 2: Hazardous Ingredients

Refer to Section 11 to identify which of these are found in each product.

CODE	INGREDIENT	CAS#	ACGIH TLV (PPM)	OSHA PEL (PPM)	STEL (PPM)	FLASH POINT (TCC/F)	VAPOR PRESSURE (mm Hg)	EMERGENCY PLAN*
5	N-BUTYL ACETATE	123-86-4	150	150	200	81	10 @ 20C	YES
7	PCBTF	98-56-6	NE	NE	NE	NE	7.6 @ 25C	NO
11	XYLENES	1330-20-7	100	100	150	77	9.5 @ 20C	YES
12	SUBSTITUTED BENZOTRIAZOLE	25973-55-1	NE	NE	NE	NE	NE	NO
36	ethyl-3-ethoxy propionate	763-69-9	NE	NE	100	136	1.5 @ 20C	YES
26	Bis(1,2,2,6,6-petametyl-4-piperidinyl) sebacate	41556-26-7	NE	NE	NE	NE	NE	NO

Section 3: Hazards Identification

Potential Health Effects:

May cause nose and throat irritation. May cause nervous system depression characterized resulting in headache, dizziness, nausea, difficulty in retaining balance, confusion, unconsciousness. Reports have associated repeated and prolonged exposure to solvents with permanent brain damage and nervous system damage. If this product contains or is mixed with an isocyanate activator/hardener, the following health effects may apply; Exposure to isocyanates (items 1-4) may cause respiratory sensitization which may be permanent. Symptoms of isocyanate exposure may be delayed for hours and can include asthma like symptoms such as shortness of breath, wheezing, and coughing. Repeated exposure to isocyanates (items 1-4) may result in permanent reduction of lung function. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of products or blends containing the ingredients (items 1-4).

Ingestion:

May result in gastrointestinal distress.

Skin or Eye Contact:

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Other Potential Health Effects in addition to those listed above:

n-butyl acetate (Item 5)

May cause abnormal liver function. Medical conditions affecting the respiratory system may be aggravated by the ingredient. Rats exposed to this chemical at high airborne levels have exhibited high frequency hearing defects but the significance of this is unknown to man. Levels of this item that were toxic to the mother were also toxic to the fetus.

PCBTF (Item 7)

People with a preexisting skin condition may have increased susceptibility to the effects of this item. Prolonged or repeated exposure may cause damage to kidneys, liver, thyroid, and or skin. Potential skin sensitizer that may cause allergic skin reactions and contact dermatitis resulting in severe irritation, dryness, and cracking. Eye contact may cause permanent eye injury. Inhalation may cause a stupor or respiratory tract irritation.

Xylene (Item 11)

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: bone marrow, cardiovascular system, central nervous system, kidneys, liver, and lungs.

Recurrent overexposure may result in liver and kidney injury. High exposures may produce irregular heartbeats. Canada classifies Xylene as a developmental toxin as high exposures to xylenes in some animal studies have been reported to cause health effects on the developing fetus/embryo. These effects were often at levels toxic to the adult animal. The significance of these effects to humans is not known. Repeated or prolonged skin contact may cause any of the following: irritation, dryness, cracking of the skin.

Substituted benzotriazole (Item 12)

The following medical conditions may be aggravated by exposure: jaundice, liver disease. Repeated or prolonged ingestion may cause any of the following: changes in the blood, liver effects.

Section 4: First Aid Measure

Inhalation:

Move affected people to fresh air immediately. If not breathing give artificial respiration and contact emergency authorities. If symptoms persist or return later contact a physician immediately.

Ingestion:

In the unlikely event of ingestion, DO NOT INDUCE VOMITING. Call a physician or the poison control hotline immediately and have a lot of all ingredients ready.

Skin or Eye Contact:

In case of eye contact immediately flush with copious amounts of water or a designated eye wash solution for at least 15 minutes and call a physician. If skin contact occurs wash the affected area thoroughly with soap and water. If irritation persists contact a physician.

Section 5: Fire Fighting Measures

Flash Point: -4 – 160°F (see section 11 for specific values)

Flammability Limits: Lower Flammability Limit – 0%
Upper Flammability Limit – 19%

Extinguishing Media: Foam, carbon dioxide (CO₂), and/or dry chemical

Fire Fighting Procedures: Full protective equipment equipped with a self contained fresh air breathing apparatus is recommended. Use water from fog nozzles to cool closed containers of these items.

Fire and Explosion Hazards:

When this product is exposed to air above its flash point vapors may be present and levels sufficient enough to burn or explode given a proper ignition source. Spray mists of this product may be flammable even below its flash point. Furthermore, closed containers of this product exposed to elevated temperatures may be sensitive to rapid release of pressure on opening or rupture of its container. Use caution when working in areas where containers may appear to be bulging or in areas where the temperature of closed containers exceed 120°F.

Section 6: Accidental Release Measures

Procedures for cleaning up spills or leaks:

Evacuate non-emergency personnel and isolate the area immediately. Ventilate area and remove sources of ignition. Prevent skin and eye contact and breathing of vapor. Emergency personnel must be outfitted with eye protection, chemical resistant gloves, protective clothing, and the proper respirator for the material released. If material does not contain or is not mixed with an isocyanate activator or hardener (any product containing item 1, 2, 3, or 4 in section 11) wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C). If the material contains, is mixed with an isocyanate (any product containing item 1, 2, 3, or 4 in section 11) activator or hardener, or the contents are unknown wear a positive-pressure, supplied-air respirator (NIOSH approved TC-19C). Take measures to confine release then cover affected area with dry absorbent. Then, releases containing isocyanate, should be saturated with a solution comprised of 90% water, 5% ammonia solution, and 5% liquid detergent solution and allowed to stand for 15 minutes. Once material has been gathered do not seal container for at least 48 hours to allow CO₂ generated from neutralization to escape. Do not allow material to enter drains or touch soil at any point. Dispose of material according to local regulations.

SECTION 7. Handling and Storage

Precautions to be taken in handling:

VAPORS MAY IGNITE EXPLOSIVELY OR CAUSE FLASH FIRE. KEEP PRODUCT AND VAPORS AWAY FROM ANY POTENTIAL OR KNOWN IGNITION SOURCES INCLUDING POSSIBLE STATIC DISCHARGE SOURCES. Vapors may spread long distances. Prevent buildup of vapors. Close container after each use. Ground containers when pouring. Wash thoroughly after handling and before eating or smoking. Do not store above 120 deg F. When transferring to another container make sure container is properly labeled to identify the hazards of the product. KEEP AWAY FROM CHILDREN.

Other precautions:

If material has dried to a solid form such as its final form of a coating do not sand, abrasive blast, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, protective eye wear, and gloves.

SECTION 8. Personal Protection

Ventilation:

Provide sufficient ventilation in volume and pattern to keep contaminants below applicable exposure limits.

Respiratory protection:

Do not breathe vapors or mists. If this product contains isocyanates or is used with an isocyanate activator/hardener, wear a positive-pressure, supplied-air respirator (NIOSH approved TC-19C) while mixing activator/hardener with paint, during application and until all vapors and spray mist are exhausted. If product does not contain or is not mixed with an isocyanate activator or hardener, a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH TC-23C) and particulate filter (NIOSH TC-84A) may be used. Follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in any area where spray mists or vapor exists. Individuals with history of lung or breathing problems or prior reaction to isocyanates should not use or be exposed vapor or spray mist if product contains or is mixed with isocyanate activators/hardeners.

Eye protection:

Goggles are preferred while handling product to prevent splashes into the eyes or vapors and spray mists from irritating the eyes. If safety glasses are substituted include splash guards or side shields.

Skin and body protection:

Chemical resistant gloves and coveralls are recommended when handling or spraying this material.

Section 9: Physical Data

Evaporation Rate:	Slower than ether	Vapor Density:	Heavier than air
Solubility in water:	none to slight	Volatiles by Volume:	45%-100%
Boiling Range:	134 – 350°F	volatiles by weight	42%-100%
Density:	6-15 lbs/gallon	Specific Gravity:	.72-1.8
VOC:	See section 11 for details		

Section 10: Stability and Reactivity

Stability

Products containing isocyanate (contains items 1,2,3, or 4 as shown in Section 11) either as part of its composition or the composition of a hardener or activator that may have been added may slowly generate carbon dioxide (CO₂) gas when exposed to water or moisture. If exposure to moisture or water is expected to do reseal containers to prevent pressure build up.

Sensitivity to Static Discharge

Products used above their flash point or spray mist from products are sensitive to static ignition sources and could explode in the presence of a static spark. Bonding and grounding should be used when transferring material.

Incompatibility (Materials to avoid): None reasonably foreseeable.

Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide, Smoke, and other harmful gases may be liberated on combustion.

Hazardous Polymerization: Will not occur.

Sensitivity to Mechanical Impact: None Known

ACGIH – American Conference of Governmental Industrial Hygienist
ANSI – American National Standards Institute
CERCLA – Comprehensive Environmental Response, Compensation, and Liability Act
CFR – Code of Federal Regulations
DOT – Department of Transportation
OSHA – Occupational Safety and Health Administration
IARC – International Agency for Research on Cancer
NIOSH – National Institute of Occupational Safety and Health
NTP – National Toxicology Program
IATA – International Air Transport Association
IMO – International Maritime Organization;
PEL – Permissible Exposure Limit
STEL – Short Term Exposure Limit
TLV – Threshold Limit Value
TWA – Time Weighted Average
TCC – Tag Closed Cup
VOC – Volatile Organic Content
HAPS – Hazardous Air Polluting Solvents;
mg/m³ – milligrams per cubic meter;
mm – millimeters;
PPM – parts per million;
PPT – parts per thousand;
SARA – Superfund Amendments and Reauthorization Act